## WEARABLE COMMUNICATIONS DEVICE

### LET'S TALK

Communicate and operate confidently with the TLK 25, a wearable WAVE PTX<sup>TM</sup> device that expands your capabilities beyond push-to-talk and doesn't limit communication to one site. Compact, powerful, rugged and equipped with an intuitive voice assistant for seamless communications, the TLK 25 is designed for ease of use, efficiency and safety. Access a communications, management and safety ecosystem in a small, intelligent device connected to your Wi-Fi network.



### LET'S TALK

### SMALL SLEEK SMART

- Lightweight, wearable design
- Durable and discreet
- Shaped for safety

### INTUITIVE VOICE ASSISTANCE

- Communications
- Device settings
- Safety features Lone worker, Fall alert
- User and device statuses
- Key Information -

Personal alert, Software updates

### PACKAGED ECOSYSTEM

Wi-Fi based and flexible

- Safety features: emergency calling, Lone Worker, Fall Alert, ambient listening
- WAVE PTX ecosystem



### DEVICE SPECIFICATIONS



#### **GENERAL SPECIFICATIONS**

Network	2.4, 5 GHz Wi-Fi
Channel Capacity	96 Channels
Contact List	300 Contacts
Dimensions	82 x 48 x 18.7mm (3.2 x 1.9 x 0.7 in.)
Weight (with Embedded Battery)	73g (2.6 oz)
Battery Capacity	1260mAh
Battery (Type Battery) Operating Hours 5:5:90 Duty Cycle	12 hours
IP Rating	IP67
Ports	USB Type-C (use for charging) 3.5mm audio jack
Sensor	Accelerometer
Apps	Powered by WAVE PTX
Encryption	AES 256

#### **AUDIO SPECIFICATIONS**

Digital Vocoder Type	OPUS
Audio Response	+1 to -3 dB
Audio Distortion at Rated Audio	<1%
Maximum Speech Loudness by Default*	115 dB SPL

### WIFI SPECIFICATIONS

Frequency Range	2.4 GHz, 5 GHz
Standards Supported	802.11 a, b, g, n, ac
Security Protocol Supported	WPA2 (personal and enterprise), WPA3 (personal)
Maximum Number of SSIDs	5

#### BLUETOOTH

Version	5.0 LE					
Range	up to 10m					
Supported Profiles	HSP, SPP, GATT					
Simultaneous Audio Connection	1					

#### **ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-20°C to 60°C (radio) -10°C to 60°C (with battery)
Storage Temperature	-40°C to 85°C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
Electrostatic Discharge	Per MIL-STD
Dust and Water Intrusion	IP67
Packaging Test	Per MIL-STD

\*Loudness performance based on TLK 25 paired with PMLN8536

#### **MILITARY STANDARDS (MIL-STD-810)**

	MIL-STD810C		MIL-STD810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	Method	Procedure	Method	Procedure	Method	Procedure	Method	Procedure	Method	Procedure	Method	Procedure
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temperature	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temperature Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	505.1	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1		507.2	II	507.3	II	507.4		507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2		509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I/-	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV
Contamination by Fluids <sup>3</sup>									504.2	II	504.3	2.2.6b



# WEAR YOUR TLK 25 THE WAY YOU WAY

BADGE CLIP: PMLN8538

For more information, please visit us at www.motorolasolutions.com/WAVEPTX



#### motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2023 Motorola Solutions, Inc. All rights reserved. 11-2023

EARPIECE: PMLN8536

#### High quality audio and operational experiences: TLK 25 Earpiece

Equipped with push-to-talk and voice assistant buttons, the TLK 25 comes with a compatible earpiece that lets users keep their device in their pocket while carrying out essential functions. Additionally, the TLK 25 supports Bluetooth 5.0 LE, offering users the flexibility to use Bluetooth earpieces or headphones for improved range, connectivity, clearer audio, and enhanced power efficiency.

HOLSTER: PMLN8537\* USB-C to USB-A CHARGING CABLE: PMKN4294

\*Not Included