



UH-RDECTREPEAT

DECT REPEATER

Extend the range of your DECT Phone, Easy and Simple. A repeater can be deployed when a need to extend the range of a DECT telephone arises. The repeater can also be utilized wherever there is a need to increase limited coverage or improve reception in remote areas.

FEATURES

STATE-OF-THE-ART REPEATER - IMPRESSIVE RANGE

UH-RDECTREPEAT

Standard DECT repeater

- Up to 6 repeaters per base station
- 2 simultaneous calls per repeater
- Automatic registration method
- 2 internal antennas

TECHNICAL SPECIFICATIONS



UH-RDECTREPEAT GENERAL FEATURES

- Worldwide DECT support
- Extending the DECT coverage
- Supports automatic handover of calls between cells
- Handling of 2 active calls simultaneously
- Up to 6 repeaters per base station
- Automatic registration method
- Environmental conditions: temp range, from -10°C to +50°C

DESIGN/SIZE

- Indoor cabinet
- Manual mounting kit
- Easily mounted on walls
- Size: 120(W) x 35(D) x 135(H)mm

POWER SUPPLY

- 230 VAC and 110 VAC versions available

FREQUENCY/COVERAGE

- Frequency bands coverage: EU/AU/NZ, US/CA, LATAM, TW
- Up to 50m indoor and 300m outdoor
- Receiver sensitivity: -92dBm
- 2 internal omni-directional antennas

STANDARDS/APPROVALS

- The DECT repeater is designed in accordance with the Digital Enhanced Cordless Telecommunications (DECT) standard
- The DECT repeater is compliant with:
 - TBR6, TBR22 (Generic Access Profile, GAP)

LED INDICATOR

- Radio link quality indication